US009575708B2

(12) **United States Patent**
Park

(10) **Patent No.: US 9,575,708 B2**
(45) **Date of Patent: *Feb. 21, 2017**

(54) **PORTABLE DEVICE AND METHOD FOR CONTROLLING THE SAME**

(71) Applicant: **LG ELECTRONICS INC.**, Seoul (KR)

(72) Inventor: **Hyorim Park**, Seoul (KR)

(73) Assignee: **LG ELECTRONICS INC.**, Seoul (KR)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 50 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **14/577,683**

(22) Filed: **Dec. 19, 2014**

(65) **Prior Publication Data**

US 2015/0130738 A1 May 14, 2015

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/408,480, filed as application No. PCT/KR2012/005136 on Jun. 28, 2012.

(30) **Foreign Application Priority Data**

May 14, 2012 (KR) 10-2012-0051093

(51) **Int. Cl.**
G06F 3/14 (2006.01)
G06F 1/16 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC ***G06F 3/1423*** (2013.01); ***G06F 1/1647*** (2013.01); ***G06F 1/1694*** (2013.01); ***G06F 1/3265*** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G06F 3/1423; G06F 1/1694; G06F 3/017; G06F 1/3265; G06F 1/3287; G06F 3/1446; G06F 1/1647; G06F 2200/1637; G09G 2320/028; G09G 2300/023; G09G 2354/00; G09G 2360/04
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,577,496 B1 * 6/2003 Gioscia G06F 1/1616 345/156
7,460,108 B2 12/2008 Tamura
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1 843 563 A1 10/2007
EP 2 341 418 A1 7/2011
(Continued)

OTHER PUBLICATIONS

Shen et al., "Double-side Multi-touch Input for Mobile Devices," CHI 2009—Digital Life, New World: Conference Proceedings and Extended Abstracts; The 27th Annual Chi Conference on Human Factors in Computing Systems, USA, Apr. 4-9, 2009, XP007912043, pp. 4339-4344.

Primary Examiner — Michael Pervan
(74) *Attorney, Agent, or Firm* — Birch, Stewart, Kolasch & Birch, LLP

(57) **ABSTRACT**

A method for controlling a portable device including first and second display units at opposing surfaces of the portable device. The method includes detecting one of a first unlock command for switching a state of the first display unit to an active state and maintaining a state of the second display unit in a locked state or a second unlock command for switching the state of the first display unit to the active state and switching the state of the second display unit to a ready-to-activate state; switching the state of the first display unit to
(Continued)